

1 1. In a heat pipe in which a boundary structure forms an
2 enclosed vapor chamber, the improvement comprising: at least
3 one mounting hole penetrating the heat pipe.

4 2. In a heat pipe in which a boundary structure forms an
5 enclosed vapor chamber, the improvement comprising: at least
6 one mounting hole penetrating the heat pipe, with the mounting
7 hole isolated from the vapor chamber by being located within a
8 sealed structure which is sealed to the boundary structure so
9 that the mounting hole through the heat pipe has no access to
10 the vapor chamber.

11 3. The heat pipe of claim 2 wherein the sealed structure is
12 a column spanning the boundary structure.

13 4. The heat pipe of claim 2 wherein the sealed structure is
14 a depression within one part of the boundary structure which
15 contacts and is bonded to another part of the boundary
16 structure.

17 5. The heat pipe of claim 2 wherein the sealed structure is
18 a lip located at an edge of the boundary structure which is
19 bonded to another lip at the edge of the boundary structure.

20 6. In a heat pipe in which a boundary structure forms an
21 enclosed vapor chamber, with a capillary wick within the heat
22 pipe attached to the part of the heat pipe which is in contact
23 with a heat source, so that the capillary wick acts as the heat
24 pipe evaporator, the improvement comprising: the capillary wick

1 being constructed with at least two separate sections of
2 different materials and with a section located at the part of
3 the heat pipe which is in contact with the heat source being
4 formed of a material with higher heat conductivity than
5 sections located at parts of the heat pipe not in contact with
6 the heat source.

7 7. The heat pipe of claim 6 wherein the section of higher
8 heat conductivity is constructed of sintered silver powder.

9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24